

Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 1 / 11

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: MAX020464S

Product name Acrimax Smalto Satinato

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses Industrial Professional Consumer

1.3. Details of the supplier of the safety data sheet

Name CROMOLOGY ITALIA S.p.A.

Full address Sede Legale: Via IV Novembre 4

District and Country 55016 Porcari LU

ITALY

Tel. 199119955 (+39)05832424

Fax 199119977

e-mail address of the competent person

responsible for the Safety Data Sheet info-sds@cromology.it

Product distribution by CROMOLOGY ITALIA S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to Numeri telefonici dei principali Centri Antiveleni italiani (attivi 24/24 ore):

Pavia); Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda - Milano); Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo); Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze); Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma); Centro Antiveleni di Roma 06 49978000

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri -

(CAV Policlinico Umberto I - Roma); Centro Antiveleni di Roma 06 68593726 (CAV Osp. Pediatrico Bambino Gesù- Roma); Centro Antiveleni

di Foggia 0881 732326 (Azienda Ospedaliero Universitaria di Foggia); Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli -

Napoli).

Per ulteriori informazioni: Cromology Italia SpA 199119955 (+39)05832424 from Monday to Friday 9:30-12:30 14:00-17:30.





Acrimax Smalto Satinato

Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments

Hazard classification and indication:

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Warning symbols: None

Hazard sentences (R): None

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words:

Hazard statements: EUH208

Contains:

1,2-BENZOISOTIAZOL-3(2H)-ONE 2-METIL-2H-ISOTIAZOL-3-ONE

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

May produce an allergic reaction

EUH210 Safety data sheet available on request.

Precautionary statements:

2.3. Other hazards

Information not available

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant



EN



CROMOLOGY ITALIA S.p.A.

Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 3 / 11

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Conc. % Classification 67/548/EEC Classification 1272/2008 (CLP)

ETHANEDIOL

CAS 107-21-1 0,00 - 0,1 Xn R22 Acute Tox. 4 H302

EC 203-473-3 INDEX 603-027-00-1

Reg. no. 01-2119456816-28-XXXX

Xn= HARMFUL

Note: Upper limit is not included into the range

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.





Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 4 / 11

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

Éire

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace

exposure limits for use with the Control of Substances Hazardous to Health

Regulations (as amended).

Code of Practice Chemical Agent Regulations 2011.

— SDS 11.0.4 EPY 1003



Acrimax Smalto Satinato

Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 5 / 11

SECTION 8. Exposure controls/personal protection

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;

Directive 2000/39/EC.

TLV-ACGIH ACGIH 2012

PIGMENT RED 101

Threshold Limit Value

Country TWA/8h Type STEL/15min mg/m3 mg/m3

WEL UK OEL. IRL. 5 **TLV-ACGIH**

TITANIUM DIOXIDE

Threshold Limit Value

Type Country TWA/8h STEL/15min mg/m3

WEL UK **OEL** IRL. TLV-ACGIH

Predicted no-effect concentration - PNEC

Normal value for the terrestrial compartment > 100 mg/kg > 1 mg/l Normal value in fresh water 0.127 mg/l Normal value in marine water > 1000 mg/kg Normal value for fresh water sediment Normal value for marine water sediment > 100 mg/kg 100 mg/kg Normal value of STP microorganisms

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers Effects on workers

Acute local Acute systemic Chronic local Chronic systemicAcute local Acute systemic Chronic local Chronic systemic Route of exposure

Oral mg/kg p.c.

10 Inhalation

mg/mc Skin



Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 6 / 11

SECTION 8. Exposure controls/personal protection

| 1.2 | -PR | OPA | NE | DIOL |
|-----|-------|-----|----|------|
| | _T T/ | | | |

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15 | min |
|------|---------|--------|-----|---------|-----|
| • • | · | mg/m3 | ppm | mg/m3 | ppm |

WEL UK 474 150

OEL IRL 10

Predicted no-effect concentration - PNEC

| Normal value for the terrestrial compartment | 50 | mg/kg |
|--|-------|-------|
| Normal value in fresh water | 260 | mg/l |
| Normal value for fresh water sediment | 572 | mg/kg |
| Normal value for water, intermittent release | 183 | mg/l |
| Normal value for marine water sediment | 57.2 | mg/kg |
| Normal value of STP microorganisms | 20000 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| | Effects on | consumers | | Effects on | workers | | |
|-------------------|-------------|----------------|---------------|-----------------------------|----------------|---------------|------------------|
| Route of exposure | Acute local | Acute systemic | Chronic local | Chronic systemicAcute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | | | | | |
| Inhalation | | | 50 | 10 | | 168 | 10 |
| | | | mg/mc | mg/mc | | mg/mc | mg/mc |

Skin

ETHANEDIOL

| Threshold Limit | | | | | | |
|-----------------|---------|-------------|-----------|--------------|-------------|------|
| Туре | Country | TWA/8 mg/m3 | Bh ppm | STEL/1 mg/m3 | 5min ppm | |
| WEL | UK | 52 | 20 | 104 | 40 | |
| OEL | IRL | 52 | 20 | 104 | 40 | SKIN |
| OEL | EU | 52 | 20 | 104 | 40 | SKIN |
| TLV-ACGIH | | | | 100(C) | | |

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

8.2. Exposure controls

RESPIRATORY PROTECTION

If workplace maximum concentration thresholds are exceeded, wear a facemask covering the nose and mouth (ref. standard EN 14387). For high concentrations in the workplace or in the case of an emergency, when exposure levels are unknown, wear an open circuit compressed air self-respirator (see standard EN 137) or an external air intake respirator with mask, partial mask or snorkel (see standard EN 138).

HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves` limit depends on the duration of exposure.

EYE PROTECTION

Use of protective airtight goggles (ref. standard EN 166) recommended.



Acrimax Smalto Satinato

Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 7 / 11

SECTION 8. Exposure controls/personal protection

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN ISO 20344). Wash body with soap and water after removing overalls.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour Various colours Odour Characteristic, light Odour threshold Not available

8,5 Melting point / freezing point Not available Initial boiling point > 100 Boiling range Not available Flash point > 60 °C Not available Evaporation Rate Flammability (solid, gas) Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available

Vapour density Relative density 1,100 kg/l 20°C Solubility Disperdibile in acqua. Not available Partition coefficient: n-octanol/water Not available Auto-ignition temperature Decomposition temperature Not available 3000 mPa.s Viscosity

Not available Explosive properties Not available Oxidising properties

9.2. Other information VOC (Directive 2004/42/EC):

50,00 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL: can absorb atmospheric humidity up to twice its own weight. Decomposes at temperatures over 200°C.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANEDIOL: risk of explosion on contact with: perchloric acid. Can react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with the air.



Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 8 / 11

SECTION 10. Stability and reactivity

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL: avoid exposure to sources of heat and naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANEDIOL: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, formaldehyde, carbon monoxide, hydrogen.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product contains sensitizing substance/s and may cause allergic reactions.

ETHANEDIOL: following ingestion it initially stimulates the CNS; later on depression results. Renal damage with anuria and uremia may occur. Symptoms of over exposure are: vomiting, somnolence, difficulty in breathing, convulsions. The lethal dose in man is approximately 1.4 l/kg. The way of entry is inhalation and ingestion.

ETHANEDIOL

LD50 (Oral) >2.000 mg/kg Rat LD50 (Dermal) 9.530 mg/kg Rabbit

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

ETHANEDIOL: easily biodegradable.

12.3. Bioaccumulative potential

ETHANEDIOL: no appreciable bioaccumulation potential (log Ko/w 1-3).

12.4. Mobility in soil

ETHANEDIOL: very mobile in soil.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.



Acrimax Smalto Satinato

Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015

SECTION 12. Ecological information

12.6. Other adverse effects Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation

1907/2006

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

VOC (Directive 2004/42/EC):

Interior/exterior trim and cladding paints for wood, metal or plastic.

VOC given in g/litre of product in a ready-to-use condition:

Limit value: 130 (2010) VOC of product: 50,00



EN



CROMOLOGY ITALIA S.p.A.

Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 10 / 11

SECTION 15. Regulatory information

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4
H302 Harmful if swallowed.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R22 HARMFUL IF SWALLOWED.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament

EN



CROMOLOGY ITALIA S.p.A.

Acrimax Smalto Satinato

MAX Revision nr.1 Dated 29/5/2015 Printed on 1/7/2015 Page n. 11 / 11

SECTION 16. Other information

- ECTION 10. Other information
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- 9. The Merck Index. 10th Edition
- 10. Handling Chemical Safety
- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 15. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

