



Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: MAX022639- MAX022676S
Product name: Paintlac Smalto Murale Opaco

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Enamel

| Identified Uses | Industrial | Professional | Consumer |
|-----------------|------------|--------------|----------|
| Paint/Coating | - | -✓ | -✓ |

1.3. Details of the supplier of the safety data sheet

Name: CROMOLOGY ITALIA SPA
Full address: Sede Legale: Via IV Novembre, 4
District and Country: 55016 Porcari LU
ITALY
Tel. 199119955 (+39)05832424
Fax 199119977

e-mail address of the competent person responsible for the Safety Data Sheet: info-sds@cromology.it

Product distribution by: CROMOLOGY ITALIA SPA

1.4. Emergency telephone number

For urgent inquiries refer to Telephone numbers of the main Italian Poison Control Centers (active 24/24 hours):
Centro Antiveleni di Pavia 0382 24444 (CAV Centro Nazionale di Informazione Tossicologica - Pavia); Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda - Milano); Centro Antiveleni di Bergamo 800 883300 (CAV Azienda Ospedaliera Papa Giovanni XXII - Bergamo); Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze); Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma); Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma); Centro Antiveleni Pediatrico di Roma 06 68593726 (CAVp Osp. Pediatrico Bambino Gesù- Roma); Centro Antiveleni di Foggia 0881 732326 (Azienda Ospedaliero Universitaria di Foggia); Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli).

For other informations: Cromology Italia SpA (+39)05832424
From Monday to Friday 9:30-12:30 14:00-17:30.

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

Hazard classification and indication:

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH208

Contains:

1,2-BENZOISOTIAZOL-3(2H)-ONE

2-METIL-2H-ISOTIAZOL-3-ONE

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

May produce an allergic reaction.

EUH210

Safety data sheet available on request.

Precautionary statements:

VOC (Directive 2004/42/EC) :

Matt coatings for interior walls and ceilings.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 30 (2010)

VOC of product : 30,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

SECTION 3. Composition/information on ingredients ... / >>**3.2. Mixtures****Contains:****Identification** **Conc. %** **Classification 1272/2008 (CLP)****Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one. [EC no. 220-239-6] (3:1)**CAS 55965-84-9 0,00 - 0,0015 Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Skin Sens. 1A H317,
Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10

INDEX 613-167-00-5

ETHANEDIOL

CAS 107-21-1 0,00 - 0,1 Acute Tox. 4 H302

EC 203-473-3

INDEX 603-027-00-1

Reg. no. 01-2119456816-28-XXXX

2-ETIL-1-ESANOLO

CAS 104-76-7 0,00 - 0,1 Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335

EC 203-234-3

Reg. no. 01-2119487289-20-XXXX

2-METIL-2H-ISOTIAZOL-3-ONECAS 2682-20-4 0,00 - 0,1 Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1,
Aquatic Chronic 2 H411

EC 220-239-6

1,2-BENZOISOTIAZOL-3(2H)-ONE

CAS 2634-33-5 0,00 - 0,025 Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10

EC 220-120-9

INDEX 613-088-00-6

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures****EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

SECTION 5. Firefighting measures ... / >>

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Wash hands after use.

7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Store the containers sealed, in a well ventilated place, away from direct sunlight.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

Glicol etilenico DNEL: Operator, long term exposure, eff. systemic inhalation 35 mg/m³; Operator, long term exposure, eff. systemic dermal 106 mg / m³; Long-term exposure consumer, eff. systemic inhalation 7 mg / m³; Operator, long term exposure, eff. systemic dermal 53 mg / m³.

8.1. Control parameters

Regulatory References:

| | | |
|-----|-------------|--|
| DEU | Deutschland | MAK-und BAT-Werte-Liste 2012 |
| ESP | España | INSHT - Límites de exposición profesional para agentes químicos en España 2015 |
| FRA | France | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 |
| GBR | | |
| GRC | Ελλάδα | ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012 |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| NLD | Nederland | Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18 |
| PRT | Portugal | Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06 |
| EU | OEL EU | Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. |
| | DNEL/DMEL | |
| | TLV-ACGH | |
| | TLV-ACGIH | ACGIH 2014 |

SECTION 8. Exposure controls/personal protection ... / >>

TITANIUM DIOXIDE

Threshold Limit Value

| Type | Country | TWA/8h mg/m ³ ppm | STEL/15min mg/m ³ ppm |
|-----------|---------|---------------------------------|-------------------------------------|
| TLV-ACGIH | | 10 | |
| VLA | ESP | 10 | |
| VLEP | FRA | 10 | |
| WEL | GBR | 4 | |
| TLV | GRC | | 10 |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value of STP microorganisms | 100 | mg/kg |
| Normal value in fresh water | >1 | mg/l |
| Normal value for fresh water sediment | >1.000 | mg/kg |
| Normal value in marine water | 0,127 | mg/l |
| Normal value for marine water sediment | >100 | mg/kg |
| Normal value for the terrestrial compartment | >100 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|-------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | | 700 mg/kg p.c. | | | | |
| Inhalation | | | | | | | 10 mg/mc | |

1,2-PROPANEDIOL

Threshold Limit Value

| Type | Country | TWA/8h mg/m ³ ppm | STEL/15min mg/m ³ ppm |
|------|---------|---------------------------------|-------------------------------------|
| WEL | GBR | 474 | 150 |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value of STP microorganisms | 20.000 | mg/l |
| Normal value in fresh water | 260 | mg/l |
| Normal value for fresh water sediment | 572 | mg/kg |
| Normal value for marine water sediment | 57,2 | mg/kg |
| Normal value for the terrestrial compartment | 50 | mg/kg |
| Normal value for water, intermittent release | 183 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | 50 mg/mc | 10 mg/mc | | | 168 mg/mc | 10 mg/mc |

SECTION 8. Exposure controls/personal protection ... / >>

ETHANEDIOL

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | |
|-----------|---------|--------|-----|---------------|-----|------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV-ACGIH | | | | 100 | | |
| | | | | (C) = CEILING | | |
| AGW | DEU | 26 | 10 | 52 | 20 | SKIN |
| MAK | DEU | 26 | 10 | 52 | 20 | SKIN |
| VLA | ESP | 52 | 20 | 104 | 40 | SKIN |
| VLEP | FRA | 52 | 20 | 104 | 40 | SKIN |
| WEL | GBR | 52 | 20 | 104 | 40 | |
| TLV | GRC | 125 | 50 | 125 | 50 | |
| VLEP | ITA | 52 | 20 | 104 | 40 | SKIN |
| OEL | NLD | 52 | | 104 | | SKIN |
| VLE | PRT | 52 | 20 | 104 | 40 | SKIN |
| OEL | EU | 52 | 20 | 104 | 40 | SKIN |

Predicted no-effect concentration - PNEC

| | | |
|--|-------|-------|
| Normal value of STP microorganisms | 199,5 | mg/l |
| Normal value in fresh water | 10 | mg/l |
| Normal value for fresh water sediment | 37 | mg/kg |
| Normal value in marine water | 1 | mg/l |
| Normal value for marine water sediment | 3,7 | mg/kg |
| Normal value for the terrestrial compartment | 1,53 | mg/kg |
| Normal value for water, intermittent release | 10 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | | 7 | | | | 106 |
| | | | | mg/mc | | | | mg/kg |
| Skin | | | | 53 | | | | 35 |
| | | | | mg/kg | | | | mg/m3 |

NERO DI CARBONE AMORFO

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | |
|-----------|---------|--------|-----|------------|-----|
| | | mg/m3 | ppm | mg/m3 | ppm |
| DNEL/DMEL | | 2 | | | |
| TLV-ACGH | | 3 | | | |
| VLA | ESP | 3 | | | |
| INRS | FRA | 3 | | | |
| WEL | GBR | 3 | | 7 | |
| OEL | ITA | 3 | | | |
| MAC | NLD | 3 | | | |

SECTION 8. Exposure controls/personal protection ... / >>**PIGMENT RED 101****Threshold Limit Value**

| Type | Country | TWA/8h mg/m ³ ppm | STEL/15min mg/m ³ ppm |
|-----------|---------|---------------------------------|-------------------------------------|
| TLV-ACGIH | | 5 | |
| MAK | DEU | 1,5 | |
| VLA | ESP | 5 | |
| VLEP | FRA | 5 | |
| WEL | GBR | 4 | |
| TLV | GRC | 10 | 10 |
| MAC | NLD | 10 | |

2-ETIL-1-ESANOLO**Threshold Limit Value**

| Type | Country | TWA/8h mg/m ³ ppm | STEL/15min mg/m ³ ppm |
|------|---------|---------------------------------|-------------------------------------|
| OEL | EU | 5,4 1 | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

SECTION 8. Exposure controls/personal protection ... / >>

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|----------------------------------|
| Appearance | Liquid |
| Colour | Various colours |
| Odour | Light, characteristic. |
| Odour threshold | Not available |
| pH | Not available |
| Melting point / freezing point | Not available |
| Initial boiling point | 100 °C |
| Boiling range | Not available |
| Flash point | > 60 °C |
| Evaporation Rate | Not available |
| Flammability (solid, gas) | Not available |
| Lower inflammability limit | Not available |
| Upper inflammability limit | Not available |
| Lower explosive limit | Not available |
| Upper explosive limit | Not available |
| Vapour pressure | Not available |
| Vapour density | >1 |
| Relative density | 1,400 kg/l 20°C |
| Solubility | Completely dispersible in water. |
| Partition coefficient: n-octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | 5000 mPa.s |
| Explosive properties | Not available |
| Oxidising properties | Not available |

9.2. Other information

VOC (Directive 2004/42/EC) : 30,00 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL: can absorb atmospheric humidity up to twice its own weight. Decomposes at temperatures over 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANEDIOL: risk of explosion on contact with: perchloric acid. Can react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with the air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL: avoid exposure to sources of heat and naked flames.

SECTION 10. Stability and reactivity ... / >>

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANEDIOL: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

SECTION 11. Toxicological information

In the absence of experimental toxicological data on the product itself, the possible dangers of the product for health, have been evaluated based on the properties of the substances contained, according to the criteria set by the reference standard for classification. Consider therefore the concentration of the individual hazardous substances mentioned in section 3, to evaluate the toxicological effects deriving from exposure to the product.

11.1. Information on toxicological effects

This product contains sensitizing substance/s and may cause allergic reactions.

ETHANEDIOL: following ingestion it initially stimulates the CNS; later on depression results. Renal damage with anuria and uremia may occur. Symptoms of over exposure are: vomiting, somnolence, difficulty in breathing, convulsions. The lethal dose in man is approximately 1,4 l/kg. The way of entry is inhalation and ingestion.

2-METIL-2H-ISOTIAZOL-3-ONE

LD50 (Oral) >2.500 mg/kg Rat (OECD 423)

LD50 (Dermal) >2.000 mg/kg Rat (OECD 402)

LC50 (Inhalation) 5,71 mg/l rat (OECD 403)

ETHANEDIOL

LD50 (Oral) >2.000 mg/kg Rat

LD50 (Dermal) 9.530 mg/kg Rabbit

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

1,2-BENZOISOTIAZOL-3(2H)-ONE

LC50 - for Fish 1,6 mg/l/96h Oncorhynchus mykiss (OECD 203)

EC50 - for Crustacea 2,94 mg/l/48h Daphnia magna (OECD 202)

EC50 - for Algae / Aquatic Plants 0,11 mg/l/72h Selenastrum capricornutum (OECD 201)

2-METIL-2H-ISOTIAZOL-3-ONE

LC50 - for Fish 8,4 mg/l/96h Oncorhynchus mykiss OECD 201

EC50 - for Crustacea 32 mg/l/48h Dafnia magna OECD 202

EC50 - for Algae / Aquatic Plants 0,157 mg/l/72h Pseudokirchneriella subcapitata (OECD 201)

SECTION 12. Ecological information ... / >>

ETHANEDIOL

| | |
|-----------------------|-------------|
| LC50 - for Fish | 72.860 mg/l |
| EC50 - for Crustacea | >100 mg/l |
| Chronic NOEC for Fish | 15.830 mg/l |

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

| | |
|-----------------------------------|---|
| LC50 - for Fish | 0,22 mg/l/96h Oncorhynchus mykiss |
| EC50 - for Crustacea | 0,12 mg/l/48h Daphnia magna |
| EC50 - for Algae / Aquatic Plants | 0,048 mg/l/72h Pseudokirchnerella subcapitata |

12.2. Persistence and degradability

ETHANEDIOL

| | |
|---------------------|-------------------|
| Solubility in water | 1000 - 10000 mg/l |
|---------------------|-------------------|

Rapidly biodegradable

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

Rapidly biodegradable

12.3. Bioaccumulative potential

ETHANEDIOL

| | |
|--|-----------|
| Partition coefficient: n-octanol/water | 1,360000- |
|--|-----------|

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.



SECTION 14. Transport information ... / >>

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation

1907/2006

None

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

SECTION 15. Regulatory information ... / >>

Information not available

VOC (Directive 2004/42/EC) :

Matt coatings for interior walls and ceilings.

This product contains biocidal products

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|---|
| Acute Tox. 2 | Acute toxicity, category 2 |
| Acute Tox. 3 | Acute toxicity, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1A | Skin sensitization, category 1A |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute toxicity, category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic toxicity, category 2 |
| H330 | Fatal if inhaled. |
| H301 | Toxic if swallowed. |
| H311 | Toxic in contact with skin. |
| H302 | Harmful if swallowed. |
| H332 | Harmful if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH208 | Contains <name of sensitising substance>. May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation

SECTION 16. Other information ... / >>

- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:



CROMOLOGY ITALIA SPA
Paintlac Smalto Murale Opaco

Revision nr.2
Dated 12/04/2017
Printed on 30/01/2018
Page n. 15 / 15

EN

SECTION 16. Other information ... / >>

The following sections were modified:
01/02/03/04/08/09/11/14/15