

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: MAX023956S
Product name: Rivital Trattamento Rivitalizzante

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Flatting for wood

Identified Uses	Industrial	Professional	Consumer
Varnish for wood	-	✓	✓
Uses Advised Against			

1.3. Details of the supplier of the safety data sheet

Name: CROMOLOGY ITALIA SPA
Full address: Sede Legale: Via IV Novembre, 4
District and Country: 55016 Porcari LU
ITALY
Tel. 199119955 (+39)05832424
Fax 199119977

e-mail address of the competent person responsible for the Safety Data Sheet: info-sds@cromology.it

Product distribution by: CROMOLOGY ITALIA SPA

1.4. Emergency telephone number

For urgent inquiries refer to: Telephone numbers of the main Italian Poison Control Centers (active 24/24 hours):
Centro Antiveleni di Pavia 0382 24444 (CAV Centro Nazionale di Informazione Tossicologica - Pavia); Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda - Milano); Centro Antiveleni di Bergamo 800 883300 (CAV Azienda Ospedaliera Papa Giovanni XXII - Bergamo); Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze); Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma); Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma); Centro Antiveleni Pediatrico di Roma 06 68593726 (CAVp Osp. Pediatrico Bambino Gesù - Roma); Centro Antiveleni di Foggia 0881 732326 (Azienda Ospedaliero Universitaria di Foggia); Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli).

For more information: Cromology Italia SpA 199119955 (+39)05832424
From Monday to Friday 9:30-12:30 14:00-17:30.

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

Hazard classification and indication:

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH208

Contains:

1,2-BENZOISOTIAZOL-3(2H)-ONE

2-METIL-2H-ISOTIAZOL-3-ONE

MISCELA DI BENZOTRIAZOLI CE N. 400-830-7

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one. [EC no. 220-239-6] (3:1)

May produce an allergic reaction.

EUH210

Safety data sheet available on request.

Precautionary statements:

VOC (Directive 2004/42/EC):

Minimal build woodstains.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 130 (2010)

VOC of product : 130,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.1. Substances**

Information not relevant



CROMOLOGY ITALIA SPA

Rivital Trattamento Rivitalizzante

Revision nr.4
Dated 20/04/2020
Printed on 16/02/2021
Page n. 3 / 15

EN

SECTION 3. Composition/information on ingredients ... / >>

3.2. Mixtures

Contains:

Identification	Conc. %	Classification 1272/2008 (CLP)
----------------	---------	--------------------------------

2-BUTOXYETHANOL

CAS	111-76-2	2,9 - 4	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	203-905-0		
INDEX	603-014-00-0		
Reg. no.	01-2119475108-36-XXXX		

2-BUTANOL

CAS	78-92-2	1,9 - 3	Flam. Liq. 3 H226, Eye Irrit. 2 H319, STOT SE 3 H335, STOT SE 3 H336, Note C
EC	201-158-5		

MISCELA DI BENZOTRIAZOLI CE N. 400-830-7

CAS	104810-48-2	0,4 - 0,7	Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC	400-830-7		
Reg. no.	01-2119472279-28-XXXX		

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-isothiazol-3-one. [EC no. 220-239-6] (3:1)

CAS	55965-84-9	0,00 - 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071, Note B
EC	611-341-5		
INDEX	613-167-00-5		

ZINC PYRITHIONE

CAS	13463-41-7	0,00 - 0,025	Acute Tox. 2 H330, Acute Tox. 3 H301, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10
EC	236-671-3		
Reg. no.	01-2119511196-46-XXXX		

2-METIL-2H-ISOTIAZOL-3-ONE

CAS	2682-20-4	0,00 - 0,0015	Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1
EC	220-239-6		

1,2-BENZOISOTIAZOL-3(2H)-ONE

CAS	2634-33-5	0,00 - 0,05	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411
EC	220-120-9		
INDEX	613-088-00-6		

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

Information not available

SECTION 4. First aid measures ... / >>

4.3. Indication of any immediate medical attention and special treatment needed
Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment.

Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters****Regulatory References:**

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR		
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
ROU	România	Monitorul Oficial al României 44; 2012-01-19
	TLV (ACGIH 9)	
	TLV-ACGIH	ACGIH 2016

SECTION 8. Exposure controls/personal protection ... / >>

2-BUTOXYETHANOL

Threshold Limit Value

Type	Country	TWA/8h mg/m ³	ppm	STEL/15min mg/m ³	ppm	
TLV-ACGIH		97	20			
AGW	DEU	49	10	196	40	SKIN
MAK	DEU	49	10	98	20	SKIN
VLA	ESP	98	20	245	50	SKIN
VLEP	FRA	49	10	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
TLV	GRC	120	25			
VLEP	ITA	98	20	246	50	SKIN
OEL	NLD	100		246		SKIN
VLE	PRT	98	20	246	50	SKIN
TLV	ROU	150	30	250	50	SKIN

Predicted no-effect concentration - PNEC

Normal value of STP microorganisms	463	mg/l
Normal value in fresh water	8,8	mg/l
Normal value for fresh water sediment	34,6	mg/kg
Normal value in marine water	0,88	mg/l
Normal value for marine water sediment	3,46	mg/kg
Normal value for the terrestrial compartment	2,33	mg/kg
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for water, intermittent release	9,1	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				6,3 mg/kg				
Inhalation	426 mg/m3			59 mg/m3	246 mg/m3	1.091 mg/m3		98 mg/m3
Skin		89 mg/kg		75 mg/kg		89 mg/kg		125 mg/kg

2-BUTANOLO

Threshold Limit Value

Type	Country	TWA/8h mg/m ³	ppm	STEL/15min mg/m ³	ppm
TLV (ACGIH 9)		150		152	

(C) = CEILING

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

SECTION 8. Exposure controls/personal protection ... / >>**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Liquid
Colour	colourless
Odour	Light of alcohol
Odour threshold	Not significant
pH	8,5
Melting point / freezing point	Not available
Initial boiling point	> 100 °C
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	>1
Relative density	1,010 20°C
Solubility	Dispersible in water Insoluble in hydrocarbons
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	15s (ISO Cup 6)
Explosive properties	Not available
Oxidising properties	Not available



CROMOLOGY ITALIA SPA

Rivital Trattamento Rivitalizzante

Revision nr.4
Dated 20/04/2020
Printed on 16/02/2021
Page n. 8 / 15

EN

SECTION 9. Physical and chemical properties ... / >>

9.2. Other information
VOC (Directive 2004/42/EC) :

130,00

g/litre

SECTION 10. Stability and reactivity

2-BUTANOLO

La miscela di alcoli butilici reagisce con ossidanti forti e con i metalli alcalini liberando idrogeno infiammabile.
Attacca diversi tipi di materie plastiche.

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.

11.1. Information on toxicological effects

ACUTE TOXICITY

SECTION 11. Toxicological information ... / >>

LC50 (Inhalation - vapours) of the mixture: >20 mg/l
LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component)
LD50 (Oral) of the mixture: >2.000 mg/kg
LD50 (Dermal) of the mixture: >2.000 mg/kg

2-METIL-2H-ISOTIAZOL-3-ONE

LD50 (Oral) >2.500 mg/kg Rat (OECD 423)
LD50 (Dermal) >2.000 mg/kg Rat (OECD 402)
LC50 (Inhalation) 5,71 mg/l/1h rat (OECD 403)

2-BUTOXYETHANOL

LD50 (Oral) 615 mg/kg Rat
LD50 (Dermal) 405 mg/kg Rabbit
LC50 (Inhalation) 2,2 mg/l/4h Rat

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)
LD50 (Oral) 66 mg/kg Rat OECD 401
LD50 (Dermal) >141 mg/kg Rat OECD 402

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

EUH208

Contains:

1,2-BENZOISOTIAZOL-3(2H)-ONE

2-METIL-2H-ISOTIAZOL-3-ONE

MISCELA DI BENZOTRIAZOLI CE N. 400-830-7

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>ASPIRATION HAZARD

Viscosity: 15s (ISO Cup 6)

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

1,2-BENZOTIAZOL-3(2H)-ONE

LC50 - for Fish	1,6 mg/l/96h Oncorhynchus mykiss (OECD 203)
EC50 - for Crustacea	3,27 mg/l/48h Daphnia magna (OECD 202)
EC50 - for Algae / Aquatic Plants	0,11 mg/l/72h Selenastrum capricornutum (OECD 201)

ZINC PYRITHIONE

LC50 - for Fish	0,15 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0,05 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,067 mg/l/72h Selenastrum capricornutum

MISCELA DI BENZOTRIAZOLI CE N. 400-830-7

LC50 - for Fish	2,8 mg/l/96h Onchorhynchus mykiss
EC50 - for Crustacea	4 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	9 mg/l/72h Pseudokirchnerella subcapitata

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-isothiazol-3-one. [EC no. 220-239-6] (3:1)

LC50 - for Fish	0,22 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0,0052 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,048 mg/l/72h Pseudokirchnerella subcapitata

12.2. Persistence and degradability

2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-isothiazol-3-one. [EC no. 220-239-6] (3:1)

Rapidly degradable

12.3. Bioaccumulative potential

2-BUTOXYETHANOL

2-BUTOSSIETANOLO: Facilmente biodegradabile (criteri OECD).

1,2-BENZOTIAZOL-3(2H)-ONE

Partition coefficient: n-octanol/water	0,7
BCF	6,95

SECTION 12. Ecological information ... / >>>**2-METIL-2H-ISOTIAZOL-3-ONE**

Partition coefficient: n-octanol/water 0,32

BCF 3,16

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

BCF 3,6

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable



CROMOLOGY ITALIA SPA

Rivital Trattamento Rivitalizzante

Revision nr.4
Dated 20/04/2020
Printed on 16/02/2021
Page n. 12 / 15

EN

SECTION 14. Transport information ... / >>>

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation

1907/2006

None

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Minimal build woodstains.

This product contains biocidal products.

SECTION 15. Regulatory information ... / >>

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances
2-BUTOXYETHANOL

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains <name of sensitising substance>. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in EIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization

SECTION 16. Other information ... / >>

- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.



CROMOLOGY ITALIA SPA

Rivital Trattamento Rivitalizzante

Revision nr.4
Dated 20/04/2020
Printed on 16/02/2021
Page n. 15 / 15

EN

SECTION 16. Other information ... / >>

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02/03/05/06/07/08/09/10/11/15