# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 1 / 13 EN

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: MAX024298S
Product name Open Space

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Wall paint

Identified Uses Industrial Professional Consumer
Paint/Coating - 

The Alice LA Consumer

Uses Advised Against

1.3. Details of the supplier of the safety data sheet

Name CROMOLOGY ITALIA SPA
Full address Sede Legale: Via IV Novembre, 4

District and Country 55016 Porcari LU

ITALY

Tel. 199119955 (+39)05832424

Fax 199119977

e-mail address of the competent person

responsible for the Safety Data Sheet info-sds@cromology.it

Product distribution by: CROMOLOGY ITALIA SPA

1.4. Emergency telephone number

For urgent inquiries refer to Telephone numbers of the main Italian Poison Control Centers (active 24/24 hours):

Centro Antiveleni di Pavia 0382 24444 (CAV Centro Nazionale di Informazione Tossicologica, Pavia): Centro Antiveleni di Milano (

Informazione Tossicologica - Pavia); Centro Antiveleni di Milano 02

66101029 (CAV Ospedale Niguarda Ca` Granda - Milano); Centro Antiveleni di Bergamo 800 883300 (CAV Azienda Ospedaliera Papa Giovanni XXII - Bergamo); Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale

Careggi - Firenze); Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma); Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma); Centro Antiveleni Pediatrico di Roma 06 68593726 (CAV Posp. Pediatrico Bambino Gesù-Roma); Centro Antiveleni di Foggia 0881 732326 (Azienda Ospedaliero Universitaria di Foggia); Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli).

For more information: Cromology Italia SpA 199119955 (+39)05832424

From Monday to Friday 9:30-12:30 14:00-17:30.





# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 2 / 13

### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments

Hazard classification and indication:

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words:

Hazard statements:

EUH208 Contains:

1,2-BENZOISOTIAZOL-3(2H)-ONE 2-METIL-2H-ISOTIAZOL-3-ONE

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6]

(3:1)

May produce an allergic reaction. **EUH210** Safety data sheet available on request.

Precautionary statements:

VOC (Directive 2004/42/EC):

Matt coatings for interior walls and ceilings.

VOC given in g/litre of product in a ready-to-use condition:

Limit value: 30 (2010) VOC of product: 30,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant



#### EN



# **CROMOLOGY ITALIA SPA**

# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 3 / 13

# **SECTION 3. Composition/information on ingredients**

3.2. Mixtures

**Contains:** 

Identification Conc. % Classification 1272/2008 (CLP)

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

CAS 55965-84-9 0,00 - 0,0015 Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Skin Sens. 1A H317,

Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071, Note B

EC 611-341-5 INDEX 613-167-00-5

2-METIL-2H-ISOTIAZOL-3-ONE

CAS 2682-20-4 0,00 - 0,0015 Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Skin Sens. 1A H317,

Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1

EC 220-239-6

1,2-BENZOISOTIAZOL-3(2H)-ONE

CAS 2634-33-5 0,00 - 0,05 Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1,

Aquatic Chronic 2 H411

EC 220-120-9 INDEX 613-088-00-6

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

Information not available

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## **SECTION 5. Firefighting measures**

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.





# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 4 / 13

### **SECTION 5. Firefighting measures**

#### 8 8

# 5.3. Advice for firefighters GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

# 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment.

Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Wash hands after use.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Store the containers sealed, in a well ventilated place, away from direct sunlight.

#### 7.3. Specific end use(s)

Information not available





# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 5 / 13

# **SECTION 8. Exposure controls/personal protection**

# 8.1. Control parameters

## Regulatory References:

ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR		
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9
		Φεβρουαρίου 2012
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF
		2011:18
ROU	România	Monitorul Oficial al României 44; 2012-01-19
	TLV-ACGIH	ACGIH 2016

### TITANIUM DIOXIDE

-		<b>-</b>		
Thres	hald	Limi	t Va	116

LL	meshou Limit value								
	Type	Country	$TWA/8h\\_{mg/m3}$	ppm	STEL/15 mg/m3	min ppm			
	TLV-ACGIH		10						
	VLA	ESP	10						
	VLEP	FRA	10						
	WEL	GBR	4						
	TLV	GRC		10					
	TLV	ROU	10		15				

Predicted no-effect conc	entration - PNEC
--------------------------	------------------

Normal value of STP microorganisms	100	mg/kg
Normal value in fresh water	>1	mg/l
Normal value for fresh water sediment	>1.000	mg/kg
Normal value in marine water	0,127	mg/l
Normal value for marine water sediment	>100	mg/kg
Normal value for the terrestrial compartment	>100	mg/kg

# Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers			Effects on		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemicAcute local	Acute systemic	Chronic local Chronic systemic
Oral				700		
- "				mg/kg p.c.		

Inhalation 10 mg/mc





# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 6 / 13

SECTION 8. Exposure controls/personal protection

#### CALCIUM CARBONATE

#### Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15 mg/m3	min ppm
TLV-ACGIH		10			
VLA	ESP	10			
WEL	GBR	4			
MAC	NLD	10			

#### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

# EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9. Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Appearance Liquid Various colours
Odour Light, characteristic



Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 7 / 13

# **Open Space**

## SECTION 9. Physical and chemical properties

Odour threshold Not significative pН 8.5 Melting point / freezing point Not available Initial boiling point > 100 Boiling range Not available Flash point > 60 °C Evaporation Rate Not available Flammability (solid, gas) Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Not available Upper explosive limit Vapour pressure Not available Vapour density

Vapour density >1
Relative density 1,450 20°C

Solubility Dispersible in water. Insoluile in hydrocarbons

Partition coefficient: n-octanol/water Not available
Auto-ignition temperature Not available
Decomposition temperature Not available
Viscosity 10000 mPa.s
Explosive properties Not available
Oxidising properties Not available

9.2. Other information VOC (Directive 2004/42/EC) :

VOC (Directive 2004/42/EC) : 30,00 g/litre

### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

### **SECTION 11. Toxicological information**

In the absence of experimental toxicological data on the product itself, the possible dangers of the product for health, have been evaluated based on the properties of the substances contained, according to the criteria set by the reference standard for classification. Consider therefore the concentration of the individual hazardous substances mentioned in section 3, to evaluate the toxicological effects deriving from exposure to the product.

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.



EN



# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 8 / 13 EN

## **SECTION 11. Toxicological information**

11.1. Information on toxicological effects

### **ACUTE TOXICITY**

LC50 (Inhalation - vapours) of the mixture: >20 mg/l

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component)

LD50 (Oral) of the mixture: >2.000 mg/kg LD50 (Dermal) of the mixture: >2.000 mg/kg

#### 2-METIL-2H-ISOTIAZOL-3-ONE

 LD50 (Oral)
 >2.500 mg/kg Rat (OECD 423)

 LD50 (Dermal)
 >2.000 mg/kg Rat (OECD 402)

 LC50 (Inhalation)
 5,71 mg/l/1h rat (OECD 403)

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no.

220-239-6] (3:1)

LD50 (Oral) 66 mg/kg Rat OECD 401 LD50 (Dermal) >141 mg/kg Rat OECD 402

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

## **RESPIRATORY OR SKIN SENSITISATION**

May produce an allergic reaction.

EUH208 Contains:

1.2-BENZOISOTIAZOL-3(2H)-ONE

2-METIL-2H-ISOTIAZOL-3-ONE

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no.

220-239-6] (3:1)

#### **GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

#### **CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

## REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

### **STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

### **ASPIRATION HAZARD**



# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 9 / 13 ΕN

SECTION 11. Toxicological information

... / >>

Viscosity: 10000 mPa.s

## **SECTION 12. Ecological information**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

1,2-BENZOISOTIAZOL-3(2H)-ONE

LC50 - for Fish 1,6 mg/l/96h Oncorhynchus mykiss (OECD 203) EC50 - for Crustacea 3,27 mg/l/48h Daphnia magna (OECD 202)

EC50 - for Algae / Aquatic Plants 0,11 mg/l/72h Selenastrum capricornutum (OECD 201)

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no.

220-239-6] (3:1)

LC50 - for Fish 0,22 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 0,0052 mg/l/48h Dafnia magna

EC50 - for Algae / Aquatic Plants 0,048 mg/l/72h Pseudokirchnereilla subcapitata

12.2. Persistence and degradability

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no.

220-239-6] (3:1)

Rapidly degradable

12.3. Bioaccumulative potential

1,2-BENZOISOTIAZOL-3(2H)-ONE

Partition coefficient: n-octanol/water 0,7 BCF 6.95

2-METIL-2H-ISOTIAZOL-3-ONE

Partition coefficient: n-octanol/water 0,32 BCF 3,16

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no.

220-239-6] (3:1)

BCF 3,6

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available



# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 10 / 13 EN

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

#### **CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

### **SECTION 15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation

1907/2006





# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 11 / 13

## **SECTION 15. Regulatory information**

None

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC):

Matt coatings for interior walls and ceilings.

This product contains biocidal products.

### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2 Acute toxicity, category 2 Acute Tox. 3 Acute toxicity, category 3 Acute Tox. 4 Acute toxicity, category 4 Skin Corr. 1B Skin corrosion, category 1B Skin Corr. 1C Skin corrosion, category 1C Eve Dam. 1 Serious eye damage, category 1 Skin Irrit. 2 Skin irritation, category 2 Skin Sens. 1A Skin sensitization, category 1A

Aquatic Acute 1Hazardous to the aquatic environment, acute toxicity, category 1Aquatic Chronic 1Hazardous to the aquatic environment, chronic toxicity, category 1Aquatic Chronic 2Hazardous to the aquatic environment, chronic toxicity, category 2

H310 Fatal in contact with skin.
H330 Fatal if inhaled.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H400 Very toxic to aquatic life.

ISDS 13.0.1 EPY 1003

#### EN



# **CROMOLOGY ITALIA SPA**

# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 12 / 13

#### **SECTION 16. Other information**

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.

**EUH071** Corrosive to the respiratory tract.

EUH208 Contains <name of sensitising substance>. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)



EN



# **CROMOLOGY ITALIA SPA**

# **Open Space**

Revision nr.4 Dated 11/06/2020 Printed on 13/11/2020 Page n. 13 / 13

### **SECTION 16. Other information** .../>

- ECTION 10. Other miormation ...
- The Merck Index. 10th EditionHandling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01/02/03/06/08/09/11/13/15

