

Name	FISS' UP
Description	Water based transparent insulating basecoat for water based paints.
Main Features	- Transparent. - Improves the surfaces absorption.
Classification (UNI 8681)	A.0.C.0.A.2.HF Single-component, physically drying, dead matt, vinylic, paint for simple surface impregnation layer, in water medium.
VOC Classification (Directive 2004/42/EC)	Primer. EU limit value for Fiss'Up (cat. A/h): 30 g/L (2010). Fiss'Up contains max 30 g/L VOC.
Application Cycle	Treated plaster: remove any peeling paintwork. New plaster and painted surfaces: putty any imperfections and sand. Then proceed to apply a coat of product.
Practical advices	Keep the tin protected from frost. Since the Fiss' Up is a transparent product, a small quantity of wall paint added before application will help to ensure correct spreading over the surface to be treated. Avoid translucent spot by increasing the dilution. Environmental and surface conditions: ambient temperature min. 5°C / max 35°C; ambient relative humidity: < 80%; surface temperature : min 5°C / max 35°C; surface humidity : < 10 % of r. h. Do not apply on surfaces exposed to sun and wind.
Safety Informations	<ul style="list-style-type: none">• Keep the tin tightly closed and protected from frost.• User's safety information are contained in the relevant safety sheet.• Empty containers and containers with traces of dried product film must be disposed of according to local regulations.

Specifications and other technical information	Method	Main Data at 20°C and 60% Relative Humidity
Density g/ml	UNI 8910	0,90 ÷ 1,10
Brookfield viscosity cps	ASTM D 2196	≈ 4000
Calculated spreading rate sq. m/l	ISO 7254	10 ÷ 12 In function of the absorption of the wall
Flash point °C	UNI 8909	Not flammable
Shelf life (in cool and dry place)	UNI 10154	At least 24 months
Touch-dry hrs		Max 0,5
Hard dry hrs		4 ÷ 6
Dry to recoat hrs		4 ÷ 6
Surface of application		Interior
Colours		Transparent
Tool cleaner		Water
Thinner		Water
Brush application volume %		1:4 ÷ 1:6

This information is based on our best technical and practical knowledge. However, since the actual conditions in which the products are used beyond our direct control, we provide no guarantee as to effectiveness of the advice and suggestions contained herein. In doubt, it is advisable to conduct preliminary tests and/or call our technical service.



Cromology. Italia. S.p.a. Legal office: Via IV Novembre 4
55016 Porcari (LU) ITALY
Tel. (+39)0583 2424
www.maxmeyer.it, E-mail: info@maxmeyer.it