```
STUCCOFORTE CLASSIC
```

## Data sheet code MAX020672T

Rev. 02 of 07.01.2021 Page 1 of 2

Name	STUCCOFORTE CLASSIC in pasta	
Description	White paste putty for wood and walls.	
Main features	- Easy to level. - Easy to sand. - Does not crack.	
Application cycle	Remove any loose or peeling paintwork. Putty all imperfections and level and smoothing with a spatula. After the product has dried (approx. 2/4 hours later), sand and level the surface. In case of elevates thickness (more than 3 mm), it is advised to fill up with more applications. After sanding and brushing the surfaces, proceed with the desired painting method.	
Practical advice	Environmental and surface conditions: room temperature: min. 5°C / max. 35°C; relative humidity: <80%; surface temperature: min. 5°C / max. 35°C; surface humidity: >10% R.H. After use and before closing the can, spread a layer of water on the surface of the product to prevent it from hardening. For subsequent uses, remove the film of water and reuse the product. Do not return dry or dirty residues to the container Clean tools with water immediately after use	
Safety data	<ul> <li>Keep the tin tightly closed, in a cool place away from heat sources.</li> <li>User safety information are contained in the related safety sheet.</li> <li>Empty containers, or with traces of dried product film, must be disposed of according to local regulations.</li> </ul>	



## STUCCOFORTE CLASSIC

## Data sheet code MAX020672T

## Rev. 02 of 07.01.2021 Page 2 of 2

Specifications and other technical information	Method	Main data at 20°C and 60% relative humidity
Coat finish and aspect gloss		Matt
Density g/ml	UNI 8910	1,780 ÷ 1,880
Viscosity		Tixotropic
Calculated spreading rate (for a thickness of 1mm) m <sup>2</sup> \ Kg		1 ÷ 2
Recommended dry film thickness microns per coat		1000 ÷ 1500
Flash point °C	UNI 8909	Not flammable
Shelf life (in cool and dry place)	UNI 10154	At least 24 months
Hard dry hrs		24
Dry to recoat hrs		6 ÷ 8
Dry to sand hrs		After 2
Surfaces of application		Interiors
Colours		White
Binder		Vinyl
Tool cleaner		Water
Spatula application		Ready to use

This information is based on our best technical and practical knowledge. However, since the actual conditions in which the products are used beyond our direct control, we provide no guarantee as to effectiveness of the advice and suggestions contained herein. If in doubt, it is advisable to conduct preliminary tests and/or call our technical service.



C.R. I. S.p.a. Sede Legale: Via IV Novembre, 4 55016 Porcari (LU) ITALY Tel. 199119955 Fax 199119977 www.maxmeyer.it, E-mail: info@maxmeyer.it