

**DECORATIVE****SHARDANA**

DESCRIPTION	Pearlescent acrylic decorative finishing with pigmented flocculus for interior.
MAIN CHARACTERISTICS	SHARDANA is a decorative finish with white and black flocculus suitable to create irregular and dotted color effects with delicate iridescent brightness. The irregularity of the design that the flocculus confer to the surface and the nuances of light make SHARDANA unique in its kind.
TINTING SYSTEM	SHARDANA is available in the bases GOLD and SILVER colorable with tinting system. Add to the chosen base of Shardana, the quantity of coloring paste indicated by the desired color formula. Mix preferably by hand with a spatula. The use of the mechanical mixer is not allowed, the possible homogenization by mixer must be carried out for a maximum of 15 seconds in order to avoid the disintegration / dissolution of the flocules
CLASSIFICATION (UNI 8681)	B.4.C.0.A.0.FA Single-component, physical drying, gloss, acrylic finishing paint in water dispersion.
CLASSIFICATION VOC (Directive 2004/42/CE)	Decorative effect coating . UE limit value for SHARDANA (cat. A/I): 200 g/L (2010). SHARDANA contains max 100 g/L di COV.
APPLICATION CYCLE	INTERIOR WALLS NEVER PAINTED Eliminate the dust and not cohesive parts, isolate with acrylic primer, if necessary fill up any imperfections (holes, cracks, etc.) with stucco, working with successive shaves and sanding it. isolate the filled parts using acrylic primer. Then apply one or two coats of PITTURA DI FONDO PER EFFETTI DECORATIVI, when it's completely dry apply SHARDANA. INTERIOR WALLS ALREADY PAINTED WITH DISTEMPER PAINTS Completely eliminate the distemper paint if it is chalking. Otherwise isolate the wall with acrylic primer. All imperfections must be levelled. Then apply one or two coats of PITTURA DI FONDO PER EFFETTI DECORATIVI, when it's completely dry apply SHARDANA. INTERIOR WALLS ALREADY PAINTED WITH WASHABLE PAINTS Eliminate the dust and not cohesive parts , if it is necessary levelled any imperfections with stucco, working with successive shaves and sanding it. isolate the filled parts using acrylic primer. Then apply one or two coats of PITTURA DI FONDO PER EFFETTI DECORATIVI, when it's completely dry apply SHARDANA For the application methods we recommend viewing the demonstration video published on the website www.maxmeyer.it
PRACTICAL ADVICES	During the application of SHARDANA with brush (Seto's), the last brush stroke must be given always in the same direction to avoid color unevenness. N.B. Do not interrupt the application halfway up the wall . Environmental and surface conditions: The substrate must be dry and clean from dust, oils or any other pollutant substances. Ambient Temperature : min. +10°C / max. +35°C Ambient Relative Humidity : < 75% Surface Temperature : min. +10°C / max. +35°C

**DECORATIVE****SHARDANA****SAFETY
PRECAUTIONS**

- Close the can immediately after use.
- Store the product in its original sealed drum protected from frost and sunshine
- The user safety information is contained in the relative data sheet.
- The empty buckets with traces of dry Product must be disposed of according to local regulations.

SPECIFICATIONS AND OTHER TECHNICAL INFORMATION	METHOD	MAIN DATA AT 20°C E 60% U.R.
Coat finish and aspect gloss	UNI 9389	Metallic effect
Density g/ml	UNI 8910	1,000 ÷ 1,100
Viscosity Brookfield cps	ASTM D 2196	15.000 ÷ 25.000
Spreading rate per coat m ² /lt	ISO 7254	4 ÷ 6
Flash point °C	UNI 8909	Not flammable
Shelf life (in a fresh and dry environment)	UNI 10154	12 months
Dry to touch hrs		2 ÷ 3
Hard Dry hrs		18 ÷ 24
Dry to recoat hrs		24
Surfaces of application		Interior
Colours		Colours of relative colour card
Binder		Acrylic
Thinner		Water
Application by brush and trowel % in volume		Ready to use, eventually dilute max 5%

Servizio Clienti

Numero Verde

800-825161

Lunedì – Venerdì 8:30-17:30



Cromology Italia S.p.a.: sede legale Via IV Novembre, 4
55016 Porcari (LU) ITALY
Tel. 199 119955 Fax 199 119977
www.maxmeyer.it, E-mail: info@maxmeyer.it