

**DECORATIVE****EVOKE MATERICO**

DESCRIPTION	Decorative, material, matt paint for interior wall surfaces .
MAIN FEATURES	EVOKE MATERICO is the ideal decorative painting for decorating rustic and opaque surfaces, thanks to its sandy and rough texture. The presence of the sand contained within it allows you to easily create multiple decorative effects. EVOKE MATERICO it is also ideal as a primer for decorative finishes
TINTING SYSTEM	EVOKE MATERICO is suitable white and can be tinted with our Tinting System.
CLASSIFICATION (UNI 8681)	B.4 C.0.A.2.HC One-component, physical drying, matt vinyl finishing paint in aqueous dispersion.
VOC CLASSIFICATION (Directive 2004/42/CE)	Matt paints for interior walls and ceilings. EU limit value of VOC for EVOKE MATERICO (cat. A/a): 30 g/L (2010) EVOKE MATERICO contains 30 g/L VOC maximum.
APPLICATION CYCLE	INTERIOR WALLS NEVER PAINTED BEFORE Thoroughly clean the surface to be treated. Level imperfections (holes, cracks, fissures) with stucco Wait for correct drying, sand and thoroughly clean again. Apply a coat of acrylic primer After 12/24 hrs apply 1 or 2 coats of EVOKE MATERICO using SETOS'PLUS paint brush INTERIOR WALLS ALREADY PAINTED If the surface has been painted with tempera and is chalking when dry, we suggest to completely remove the paint. In case the paint is well anchored to the surface, thoroughly clean the surface and apply a coat of acrylic primer. After 12/24hrs apply 1 or 2 coats of EVOKE MATERICO using SETO'S PLUS paint brush. In case more EVOKE MATERICO is needed, it is possible to apply a second coat
PRACTICAL ADVICES	Stir thoroughly before use. The surface must be cured, clean, dry and without loose parts Environmental and surface conditions: room temperature: min. +5°C / max. +35°C; relative humidity: < 80%; surface temperature: min. +5°C / max. +35°C; surface humidity: < 10 with respect to relative humidity. Apply on surfaces protected from sun and wind.

**DECORATIVE****EVOKE MATERICO****SAFETY
PRECAUTIONS**

Keep the tin sealed and protected from frost.
Safety information for users is included in the related safety sheet.
Empty containers, or with traces of dried product film, must be disposed of according to local regulations.

CHARACTERISTICS AND OTHER TECHNICAL INFORMATIONS	METHOD	MAIN DATA AT 20°C AND 60% R.H.
Appearance and finish		Matt
Density g/ml	UNI 8910	1,550 ÷ 1,610
Viscosity Brookfield cps		4000 ÷ 5000
Spreading rate per coat m ² \ Lt	ISO 7254	8 ÷ 10
Flash point °C	UNI 8909	Non flammable
Shelf life (in cool and dry place)	UNI 10154	At least 24 months
Dry to touch hrs		Max 1h
Hard Dry hrs		Max 24h
Dry to recoat hrs		4 ÷ 5
Application surface		Interior
Colours		White and colours obtained with tintometric system.
Tool cleaning		Water
Binder		Vinyllic
Diluent		Water
Application by SETOS PLUS paint brush		Ready to use

Servizio Clienti

Numero Verde

800-825161

Lunedì – Venerdì 8:30-17:30



Cromology Italia S.p.a.: sede legale Via IV Novembre, 4
55016 Porcari (LU) ITALY
Tel. 199 119955 Fax 199 119977
www.maxmeyer.it, E-mail: info@maxmeyer.it