


REWIND - REMOVABLE FILM

Description:	Peel-off paint with a polyurethane resin base in aqueous phase		
Intended use	Interior use <ul style="list-style-type: none"> • Never painted walls • Walls painted with tempera paint • Walls painted with washable water paint 		
Main characteristics	<ul style="list-style-type: none"> • Base coat product easily applied with a roller • Elastic film formulated to remove paints for being painted on top, resistant to the traction required for being removed • Can be removed from masonry walls or plasterboard walls, irrespective of whether smoothed flush or already painted, even a long time after application • Can be painted over with common water-based paints and ATYPIC decorative paints 		
Main technical data	Technical data	Method	Main data at 20 °C and 60% R.H.
	Spreading rate per coat	7254 ISO	8 - 10 m ² /litre
	Dry-to-touch		1 h
	Dry in depth		24 h
	Painting over		12 h
Available colours:	transparent		
APPLICATION			
Dilution and preparation of the product	<ul style="list-style-type: none"> • Application with roller: ready for use 		
Application instruments	<ul style="list-style-type: none"> • Roller 		
Preparation of the base	<ul style="list-style-type: none"> • INTERIOR WALLS NEVER PAINTED (seasoned smooth-plaster, prefabricated panels, new plaster, plasterboard). Brush to remove dust and any peeling layers. Level out any imperfections with STUCCOFORTE paste. After at least 6 hours clean thoroughly by smoothing the surface with sandpaper. Apply one coat of FISS'UP or MAXFIX ACRYLIC, appropriately diluted. Once the base is dry, apply 1-2 coats of white CASACOLOR. • INTERNAL WALLS PAINTED WITH TEMPERA PAINT. Clean the surface thoroughly of all dust or dirt and fill in any imperfections with STUCCOFORTE paste, then sand and dust. After sanding, insulate the entire surface with FISS'UP or MAXFIX ACRYLIC, appropriately diluted. 		



	<ul style="list-style-type: none"> INTERNAL WALLS PAINTED WITH WASHABLE WATER-BASED PAINT. Accurately clean the surface, fill any imperfections with SUPER PASTE, then sand and dust. Insulate the stuccoed walls with FISS'UP or MAXFIX ACRYLIC, appropriately diluted.
Application system	Once the primer is dry, apply two coats of REWIND with the roller, waiting 12 hours between each coat. At this point, the surface will be ready for the application of ATYPIC decorative paint.
Application conditions	<ul style="list-style-type: none"> The base must be dry, free of dust, grease, and any other polluting substances. Ambient temperature: min. +10 °C / max. +35 °C. Relative humidity of the environment: <75% Temperature of the base: min. +10 °C / max. +35 °C Humidity of the base: < 10 R.H. Do not apply on bases exposed to direct sunlight or strong wind.
Known incompatibilities	None. For any use other than that indicated in this technical datasheet, please contact our Technical Service.
Cleaning the instruments	With water
Safety precautions	<ul style="list-style-type: none"> Store the container tightly sealed, away from heat sources and protected from frost and direct sunlight. The safety information for the user is contained in the relevant safety datasheet Empty containers or containers with slight traces of residual dried product or film must be disposed of according to local regulations.
Warnings	<p>This product is not suitable for removing "thick" decorative products such as stucco or marble applications.</p> <p>For correct storage of the product, after using Rewind it is recommended to clean the edges of the container carefully before closing it again.</p>
ITEM SPECIFICATION	
	<p>Elastic polyurethane primer film applicable with a roller, formulated to remove traditional organic paints and ATYPIC decorative paints applied on top. Not suitable for removing "thick" decorative products such as stuccoes or marble applications.</p> <p>Suitable for application on masonry walls or plasterboard walls, irrespective of whether shaved smooth, or already painted.</p> <p>Rewind is applied with a roller in two coats, 12 hours apart, after application of a fixative (Maxfix type) or washable paint (Casacolor type). Indicative yield equal to 4 - 5 m²/litre per coat.</p> <p>Price on site is €_____ per square metre including materials, labour and excluding scaffolding, protections and any surface preparation.</p>



OTHER INFORMATION

VOC classification (Directive 2004/42/EC)	Fixative primers. EU Limit value of VOCs for REWIND (cat. A/h): 30 g/L (2010). REWIND contains max. 30 g/L of VOCs.		
Other technical information	Technical data	Method	Main data at 20 °C and 60% R.H.
	Volume mass	UNI 8910	1,000-1,040 g/ml
	Brookfield viscosity	ASTM D 2196	15.000-20,000 cPs
	Flash point	UNI 8909	Non-flammable
	Shelf life	UNI 10154	At least 24 months

All the technical indications contained herein which are the result of our best experience, are indicative and do not constitute a guarantee of the results. The data and methods shown on this datasheet can be changed at any time in accordance with any changes in the production technology. The application of the products takes place outside our control and therefore falls under the exclusive responsibility of the customer. The correct use of the materials presupposes full observance of the general use prescriptions reported on the GENERAL CONSIDERATIONS page of the PRODUCT INFORMATION SHEET and in particular what is indicated in this sheet, especially with regard to the preparation and suitability of the bases. The technical service of Cromology Italia S.p.A. is at the users' disposal to provide additional information to that reported herein.
THIS TECHNICAL DATA SHEET CANCELS AND REPLACES ANY PREVIOUS EDITION.

Servizio Clienti

Numero Verde

800-825161

Lunedì – Venerdì 8:30-17:30



Cromology Italia S.p.a.: sede legale Via IV Novembre, 4
55016 Porcari (LU) ITALY
Tel. 199 119955 Fax 199 119977
www.maxmeyer.it, E-mail: info@maxmeyer.it