

## NATURWAX

### PROTECTIVE FINISHES



#### PRODUCT DESCRIPTION

- Description** Natural protective wax for spatulated finishes and stuccoes.
- Intended use** Indoors
- Vertical wall surfaces and ceilings with lime-based decorative finishes.
- Main features**
- It gives the substrate shine and increases the water repellency of the finish without significantly altering the breathability.
  - It protects the surfaces treated with it.

#### Main technical data

Technical information	Method	Main data at 20°C and 60% of R.H.
Appearance and finish		Whitish colour paste
Consumption per coat	ISO 7254	0.07÷0.08 L/m <sup>2</sup>

**Available colours** Transparent

#### LAYING

- Dilution and preparation of the product**
- Ready to use; it can also be diluted with water
  - If the product is too fluid (typical of the summer period) it is advisable to thicken it in the refrigerator or in a very cool place.
  - Stir thoroughly before application.

**Application tools** Application with rag, pad or trowel.

**Preparation of the substrate** WALL SURFACES PROTECTED WITH LIME-BASED FINISHES:  
Substrates must be cured, clean and free from any loose parts and/or rising damp. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.

**Application system** ONLY FOR INTERIORS:  
Apply with a rag, pad or single-hand trowel in a very thin layer. When the product is completely dry (after 12/24 hours) polish with a soft cloth or an orbital polisher at low speed.

- Touch dry: 10 h
- Dry in depth: 12÷24 h
- Overcoat: 12÷24 h

### Conditions of application

- Conditions of the environment and of the substrate: the substrate must be dry, free from rising damp, dust, flaking and greasy parts.
- Ambient and substrate temperature: min. +5°C / max. +35°C in the first 24 hours after application.
- Relative humidity of the environment: < 75%.
- Substrate humidity: < 10% of R.H.
- New finishes must be perfectly dry and seasoned.

### Practical advice

- Do not apply on surfaces exposed to direct sunlight or in the presence of strong drafts.
- Excess material can cause uneven effects and/or whitish halos.
- Store the product in its original container at a temperature between +5°C and +35°C.

### Known incompatibilities

None.  
For any use other than that indicated in this technical data sheet, contact our Technical Assistance Service.

### Cleaning of tools

With hot soapy water immediately after use.

### Safety Precautions

- Close the jar immediately after use.
- Keep it tightly closed, undiluted, away from heat sources, protected against frost and direct sunlight.
- The safety information for the user is contained in the relevant safety data sheet
- Empty containers or containers with slight traces of dried film of residual product must be disposed of in compliance with local regulations.

### Warnings

None

## ITEM SPECIFICATIONS

Application of NATURWAX, natural protective wax, specifically designed for use on spatulated finishes and lime-based stuccoes.  
NATURWAX is applied with a rag, pad or trowel, with an indicative yield of 0.07 ÷ 0.08 L/m<sup>2</sup>, depending on the absorption of the substrate.  
Price on site € \_\_\_\_\_ per m<sup>2</sup> including materials, labour, and excluding scaffolding, protections and any surface preparation.

## OTHER INFORMATION

### VOC classification (Directive 2004/42/EC)

Out of the scope

### Other technical information

Technical information	Method	Main data at 20°C and 60% of R.H.
Density	ISO 2811-1	0.87÷0.91 g/ml
Brookfield viscosity	ASTM D 2196	Paste

Flash point	UNI 8909	Not inflammable
Storage life	UNI 10154	At least 24 months

All the technical indications contained herein are the result of our best experience, are indicative and do not constitute a guarantee of results. The data and methods shown on this technical data sheet can be modified at any time depending on any change in production technologies. The application of the products takes place outside our control and therefore falls under the sole responsibility of the customer. The correct use of the materials assumes compliance with the general requirements for use set out in the GENERAL CONSIDERATIONS page of the PRODUCT INFORMATION SHEETS collection and in particular with what is indicated in this sheet, especially with regard to the preparation and suitability of the supports. The technical service of Cromology Italia spa is available to users to provide additional information to that reported here. THIS DATA SHEET REPEALS AND REPLACES ANY PREVIOUS EDITION.

**CROMOLOGY ITALIA SpA ORGANISATION WITH QUALITY, SAFETY AND ENVIRONMENTAL MANAGEMENT SYSTEM ISO 9001, OHSAS 18001, ISO 14001 CERTIFIED BY BUREAU VERITAS SpA.**

**PROFESSIONAL USE ONLY**