

MARMORIN SATIN

Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 1/15

New emission!

Safety Data Sheet
According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 455619

Product name MARMORIN SATIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses Industrial Professional Consumer

Paint / Coating - PC: 9a.

Uses Advised Against

All uses other than painting in construction.

1.3. Details of the supplier of the safety data sheet

Name CROMOLOGY ITALIA S.P.A.

Full address Via IV Novembre, 4
District and Country 55016 Porcari (LU)

Italia

itaiia

Tel. 199.11.99.55 Fax 199.11.99.77

e-mail address of the competent person

responsible for the Safety Data Sheet info-sds@cromology.it

1.4. Emergency telephone number

For urgent inquiries refer to Contact your local poison control centre.

For more information: Cromology Italia SpA Phone +39 05832424

from Monday to Friday 9:30-12:30 14:00-17:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 Causes serious eye damage. Skin irritation, category 2 H315 Causes skin irritation.

2.2. Label elements



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 2/15 New emission!

MARMORIN SATIN

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H318 Causes serious eye damage.

H315 Causes skin irritation.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water / . . .

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P501 Dispose of contents/container according to local regulation.

Contains: CALCIUM HYDROXIDE

VOC (Directive 2004/42/EC):

Interior matt walls and ceilings (Gloss < 25@60°).

VOC given in g/litre of product in a ready-to-use condition : 30,00 Limit value: 30,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024
Page n. 3/15

New emission!

MARMORIN SATIN

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

CALCIUM HYDROXIDE

INDEX - 18 ≤ x < 19.5 Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335

EC 215-137-3 CAS 1305-62-0

REACH Reg. 01-2119475151-45-

XXXX

CRYSTALLINE SILICA (BREATHABLE FRACTION)

INDEX - 0,1 ≤ x < 0,15 STOT RE 1 H372

EC 238-878-4 CAS 14808-60-7 ZINC PYRITHION

INDEX 613-333-00-7 0 ≤ x < 0,025 Repr. 1B H360D, Acute Tox. 2 H330, Acute Tox. 3 H301, STOT RE 1 H372,

Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1000, Aquatic Chronic 1 H410

M=10

EC 236-671-3 LD50 Oral: 221 mg/kg, LC50 Inhalation mists/powders: 0,14 mg/l/4h

CAS 13463-41-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT



Dated 10/07/2023 Printed on 01/07/2024 Page n. 4/15

New emission!

Revision nr. 1

MARMORIN SATIN

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)



Revision nr. 1

Dated 10/07/2023 Printed on 01/07/2024

Page n. 5/15

New emission!

MARMORIN SATIN

See the exposure scenarios attached to this safety datasheet.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

ESP España Límites de exposición profesional para agentes químicos en España 2021

France Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

FRA ITA EU

Decreto Legislativo 9 Aprile 2008, n.81

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983;

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. Italia OEL EU

TLV-ACGIH ACGIH 2022

CRYSTALLINE SILICA (BREATHABLE FRACTION) Threshold Limit Value							
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLA	ESP		0,05			RESP	
VLEP	FRA	0,1				RESP	
VLEP	ITA	0,1				RESP	
OEL	EU	0,1				RESP	
TLV-ACGIH		0,025				RESP	

Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLEP	ITA	1		4			
OEL	EU	1		4			
TLV-ACGIH		5					
Predicted no-effect	ct concentration - PNE	EC					
Normal value in fr	esh water			0,49	mg/l		
Normal value in marine water				0,32	mg/l		
Normal value of STP microorganisms				3	mg/l		
Normal value for t	the terrestrial compart	ment		1080	mg/l		

Health - Derived no-effect level - DNEL / DMEL									
	Effects on				Effects on				
	consumers				workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic	
				systemic		systemic		systemic	
Oral	NEA	NPI	NEA	NPI					
Inhalation	4 mg/m3	NPI	1 mg/m3	NPI	4 mg/m3	NPI	1 mg/m3	NPI	
Skin	VND	NPI	VND	NPI	VND	NPI	VND	NPI	

Legend:



Dated 10/07/2023
Printed on 01/07/2024
Dogo n 6/15

Revision nr. 1

New emission!

MARMORIN SATIN

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

When choosing risk management measures and operating conditions, consult the exposure scenarios attached.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with chemical resistant gloves (EN 374).

In the case of mixtures, the resistance of work gloves to chemical agents must be checked before use as it is not always predictable.

Materials also suitable for direct and prolonged contact, it is recommended: protection factor 6,> 480 minutes of permeation time (EN 374); neoprene, nitrile rubber and others. Additional information: Information is based on our experience, bibliographic data and information from glove manufacturers, or derived from substances / mixtures of similar composition. The duration of use of a protective glove can be influenced by various factors such as temperature and therefore in practice significantly lower than the permeation time detected by the test.

Due to the great variety of types, it is advisable to observe the instructions for use of the glove manufacturers.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

For information on controlling environmental exposure, see the exposure scenarios attached to this safety datasheet.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties



Revision nr. 1

Dated 10/07/2023 Printed on 01/07/2024

Page n. 7/15 New emission!

MARMORIN SATIN

Properties Value Information Appearance . paste Temperature: 20 °C white, various Colour

Odour light, characteristic

< 5 °C 100 °C Melting point / freezing point Method:Derived Initial boiling point Method:Derived Flammability not flammable Method:Derived not applicable Lower explosive limit

Upper explosive limit not applicable

Method:Derived Flash point

Auto-ignition temperature not applicable Decomposition temperature not applicable

Method:ISO 19396-1 рΗ 12 Concentration: 100 %

Temperature: 20 °C

not available Reason for missing data: Not significant data Kinematic viscosity

for classification Dynamic viscosity 80000 mPa.s Method:ISO 2884-1 Temperature: 20 °C

Solubility die-dispersible in water, Temperature: 20 °C

insoluble in hydrocarbons Partition coefficient: n-octanol/water not applicable

Vapour pressure 23 hPa Substance:WATER

Temperature: 20 °C Density and/or relative density 1,63 kg/l Method:ISO 2811-1 Temperature: 20 °C

Relative vapour density >1 Method:Derived Temperature: 20 °C

Particle characteristics not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC): 1,84 % 30,00 g/litre

VOC (volatile carbon)

SECTION 10. Stability and reactivity

10.1. Reactivity

Substances to be avoided: acids. Conditions to avoid: frost and strong heat. In case of dilution with water, the product can be heated.

10.2. Chemical stability

The product is stable under normal conditions of use and storage. Avoiding high temperatures can cause thermal decomposition.



Dated 10/07/2023
Printed on 01/07/2024

Revision nr. 1

Page n. 8/15 New emission!

MARMORIN SATIN

10.3. Possibility of hazardous reactions

See paragraph 10.1

10.4. Conditions to avoid

Avoid heating the product.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

Due to thermal decomposition or in the event of fire, gases and potentially harmful to health can be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

CALCIUM CARBONATE

LD50 (Oral): 6450 mg/kg Rat

CALCIUM HYDROXIDE

LD50 (Dermal): > 25000 mg/kg Rabbit (OECD 402)



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 9/15 New emission!

MARMORIN SATIN

LD50 (Oral):

> 2000 mg/kg Rat (OECD 425)

ZINC PYRITHION

LD50 (Oral): LC50 (Inhalation mists/powders): 221 mg/kg 0,14 mg/l/4h

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 10/15 New emission!

MARMORIN SATIN

CALCIUM HYDROXIDE

LC50 - for Fish 50,6 mg/l pesci di acqua dolce.

EC50 - for Crustacea > 49,1 mg/l/48h Dafnia

EC50 - for Algae / Aquatic Plants > 184,57 mg/l/72h Algae

ZINC PYRITHION

LC50 - for Fish 0,0104 mg/l/96h Brachydanio rerio (OECD 203)
EC50 - for Crustacea 0,0006 mg/l/48h RAC-Opinion 2018 (US-EPA 123-2)

EC50 - for Algae / Aquatic Plants 0,0013 mg/l/72h Selenastrum capricornutum (OECD 201)

Chronic NOEC for Fish 0,00125 mg/l 72h Brachydanio rerio (OECD 215)

Chronic NOEC for Crustacea 0,0022 mg/l 21d Daphnia Magna

Chronic NOEC for Algae / Aquatic Plants 0,00046 mg/l 96h Skeletonema costatum

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

ZINC PYRITHION

Partition coefficient: n-octanol/water 1,21 Log Kow n-octanol/water S2781

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 11/15 New emission!

MARMORIN	SATIN

The product is not dangerous unde	r current provisions	of the Code of Internati	onal Carriage of	Dangerous (Goods by Road	(ADR) and	by Rail (RID), of
the International Maritime Dangeroເ	is Goods Code (IMD	G), and of the Internation	nal Air Transpor	t Association	(IATA) regulatio	ns.		

CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.
SECTION 14. Transport information
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.
14.1. UN number or ID number
not applicable
14.2. UN proper shipping name
not applicable
14.3. Transport hazard class(es)
not applicable
14.4. Packing group
not applicable
14.5. Environmental hazards
not applicable
14.6. Special precautions for user
not applicable
14.7. Maritime transport in bulk according to IMO instruments



INCVISION	1111.	

Dated 10/07/2023

Printed on 01/07/2024

Page n. 12/15

New emission!

MARMORIN SATIN

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Interior matt walls and ceilings (Gloss < 25@60°).

Contains biocidal products



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 13/15 New emission!

MARMORIN SATIN

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

CALCIUM HYDROXIDE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 1B Reproductive toxicity, category 1B

Acute Tox. 2 Acute toxicity, category 2
Acute Tox. 3 Acute toxicity, category 3

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

Eye Dam. 1 Serious eye damage, category 1

Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H360D May damage the unborn child.

H330 Fatal if inhaled.
H301 Toxic if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Use descriptor system:

PC 9a Coatings and paints, thinners, paint removers

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024 Page n 14/15

New emission!

MARMORIN SATIN

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP) 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- **FCHA** website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11. Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.



Revision nr. 1

Dated 10/07/2023

Printed on 01/07/2024

Page n. 15/15 New emission!

MARMORIN SATIN

Exposure Scenarios

Product MARMORINO D BIANCO Scenario Title Precal 54 CALCE AEREA

Revision nr. File