

PUNTI LUCE

ADDITIVES

PRODUCT DESCRIPTION

Description Glitter for a decorative effect in polyethylene with an epoxy resin base, enhances the finish by creating a shimmering effect.

Intended use Indoors

- Water-based paints
- Enamels
- Decorative

Main features

- No substances of animal origin
- Square and hexagonal shapes
- Different sizes and thicknesses depending on colour

Main technical data

Technical information	Method	Main data at 20°C and 60% of R.H.
Appearance and finish		Aged appearance
Melting temperature		>250°
Lightfastness		5/6 (good)
Specific weight		1.4 g/cm ³

Available colours Silver

LAYING

Additive and preparation of the product

- Stir thoroughly before application

Application tools

- Depends on finish in use

Preparation of the substrate NEW SUBSTRATE: brush surfaces and consolidate by applying a suitably diluted coat of fixative (such as PRIMER ACQ)

OLD PAINTINGS:
if absorbent, fix suitably with primer (such as PRIMER ACQ);
if flaking, remove mechanically, brush the substrate and fix with primer (such as PRIMER ACQ)

Conditions of application

- The substrate must be cured, clean and free from peeling parts, rising damp and grease.
- New plasters should be left to cure for at least 4-5 weeks.
- Ambient and substrate temperature:
- Check the data contained on the Technical Data Sheet of the finish used

Practical advice Store the product in its original container at a temperature between +5°C and +35°C.

- Safety Precautions**
- Close the jar immediately after use.
 - Store tightly closed, away from sources of heat, protected from frost and direct sunlight.
 - The safety information for the user is contained in the relevant safety data sheet
 - Containers that are empty or almost empty must be disposed of according to local regulations

None

Warnings

ITEM SPECIFICATIONS

PUNTI LUCE for a decorative effect consisting of polyethylene glitter with an epoxy resin base, to be added to finishes to achieve a shimmering, decorative effect to enhance interior finishes.

The additive is to be mixed with the finish, to applyof g/L.

Price on site € _____ per m² including materials, labour, and excluding scaffolding, protections and any surface preparation.

All the technical indications contained herein are the result of our best experience, are indicative and do not constitute a guarantee of results. The data and methods shown on this technical data sheet can be modified at any time depending on any change in production technologies. The application of the products takes place outside our control and therefore falls under the sole responsibility of the customer. The correct use of the materials assumes compliance with the general requirements for use set out in the GENERAL CONSIDERATIONS page of the PRODUCT INFORMATION SHEETS collection and in particular with what is indicated in this sheet, especially with regard to the preparation and suitability of the supports. The technical service of Cromology Italia spa is available to users to provide additional information to that reported here. THIS DATA SHEET REPEALS AND REPLACES ANY PREVIOUS EDITION.

CROMOLOGY ITALIA SpA ORGANISATION WITH QUALITY, SAFETY AND ENVIRONMENTAL MANAGEMENT SYSTEM ISO 9001, OHSAS 18001, ISO 14001 CERTIFIED BY BUREAU VERITAS SpA.

FOR PROFESSIONAL USE